



RJ Works Sdn Bhd
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my



Silkcoat Effect Paints Marmarito Paints 4kg Client Information Pack (110 sq ft)



DESCRIPTION: **Marmarito** is an Acrylic Copolymer binder based, marble patterned decorative interior wall paint.

CHARACTERISTICS:

- Harmless to people and environmental friendly through its water based content
- Suits your personal pleasure with its marble pattern, and velvety structure
- High covering ability and leaves no cracks
- Easy cleanable through glassy surface.

APPLICATION SURFACES:

After surface preparation, **Marmarito** can be applied on a wide range of interior surfaces such as old painted surfaces, concrete, plaster, rendering, cement board, wallpaper, glass textile etc.

TECHNICAL INFORMATION

Structure: Styrene Acrylic

Coverage (for 4kg): 10 m² / 110 sq ft

Thinner: No thinning, ready to-use

Drying: Touch dry: after 30-45 min, Dust repulsive: after 1-1.5 hour, Hard dry: after 24 hours

Rosaline 0199000188 Email : rosalin@rjworks.com.my
Dennis 0169839715 Email: mcmderr@rjworks.com.my
www.rjworks.com.my





RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

PACKAGE

Package Includes:

1. 1 x 4kg of **Marmarito Effect Paint** (160 sq ft)
2. 1 x **Silkcoat Macun Pack** (where surfaces are not smooth)
3. 1 x **Marmarito Primer Pack** for 160 sq ft (in case of old or painted surfaces)
4. 1 x **Silkcoat Putty Primer Pack** (in case of old putties on surfaces)
5. 1 x **Silkcoat Izolac Pack** (where a glazed finish surface is desired)
6. 2 x **Marmarito** Application Decorative Trowel
7. 2 x Drop sheets (for floor and furniture protection)
8. 2 x Masking Tape Rolls
9. 6 x sheets sandpaper (2 x 100 grain, 2 x 80 grain, 2 x 70 grain)
10. 1 x sanding block

APPLICATION INSTRUCTIONS

INSTRUCTIONAL VIDEOS

<https://www.youtube.com/watch?v=FAiv-hI7eAs&t=8s>

<https://www.youtube.com/watch?v=WnHcu-x0KCo>

SURFACE PREPARATION:

- The surface must be cleared of any oil, dirt or dust and swollen and old paintings must be scraped off - surface must be clean, dry and solid.
 - In case the surface is not smooth, first apply **Silkcoat Dahili Acrylic Macun** to obtain a problem-free surface for topcoat application
- A smooth and glazed surface can be obtained by applying **Silkcoat Izolac** before Marmarito application
- Smooth but old painted, synthetic and dirty surfaces should be obtained by applying **Silkcoat Universal Primer**
- A surface which has been puttied should be prepared by applying **Silkcoat Putty Primer**



PRODUCT PREPARATION:

1. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying
2. Before using **Marmarito**, it should be mixed until it becomes completely homogenous
3. If applied on very bright and glassy surfaces, a solid surface should be formed by sanding the surface first to ensure better adhesion.

APPLICATION:

1. Place drop sheets on floor and over any exposed furniture under surface to be painted
2. Apply masking tape to all corners and edges at boundaries of areas to be painted
3. Where necessary on old or painted surfaces, apply a single layer of **Silkcoat Universal Primer**
4. Silkcoat **Marmarito** can be applied (without diluting) by use of decorative trowel in two coats
5. Leave minimum 4 hours between coats depending on weather conditions
6. After 2nd coat application is dry, **Marmarito** is applied with trowel (without diluting) again giving both diagonal and vertical-horizontal non-continuous trowel strikes to make the material textured on the surface
7. As a last step, the entire surface is shined by putting pressure on the trowel with up-down and right-left circular movements
8. After application, tools should be cleaned with water.

SAFETY AND PERSONAL PROTECTION DURING USE

- Avoid getting eye and skin contact. In case wash with plenty of water
- Preserve in a tightly closed container
- Keep out of the reach of children



RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

SAFE DISPOSAL OF WASTES

- Dispose of properly by washing all equipment and disposing of buckets etc in plastic recycling unit – DO NOT DUMP INTO SEWER SYSTEM

STORAGE:

- Keep in a cool and clean place away from direct sunlight
- NB: It can be stored unopened 1 year at room temperature