



**RJ Works Sdn Bhd**  
(762722-K)  
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.  
Tel : 03-78317087 Website : [www.rjworks.com.my](http://www.rjworks.com.my)

#### Metalico



5500



5511



5515



5518



5527



5529



5553



5561



5572

## Silkcoat Effect Paints Metalico Paint 3kg Client Information Pack (190 sq ft)

**DESCRIPTION:** **Metalico** is a pure Acrylic binder based, psoriasis additive, pearl elegance decorative interior wall paint.

#### CHARACTERISTIC:

- Thanks to its pearl-like structure, **Metalico** offers a bright and special look like pearls, allowing for different pattern applications.
- Harmless to people and environmental friendly through its water based content

#### APPLICATION SURFACES:

Can be applied on a wide range of interior old painted surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

#### TECHNICAL INFORMATION

Structure: Pure Acrylic

Coverage (for 3 kg): 18 m<sup>2</sup> / 190 sq ft (Wood pattern and similar), 60 m<sup>2</sup> / 600 sq ft (Leopard pattern and similar)

Thinner: Water; Thinning Ratio: 10% max.(with clean water)

Drying: Touch dry: after 15-20 minutes, Dust repulsive: after 1 hour, Hard dry: after 24 hours



**RJ** Works Sdn Bhd  
(762722-K)  
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.  
Tel : 03-78317087 Website : [www.rjworks.com.my](http://www.rjworks.com.my)



**RJ Works Sdn Bhd**  
(762722-K)  
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.  
Tel : 03-78317087 Website : [www.rjworks.com.my](http://www.rjworks.com.my)

## PACKAGE

Package Includes:

1. 1 x 3kg of **Metalico Effect Paint** (225 sq ft)
2. 1 x **Metalico Primer Pack** for 225 sq ft
3. 1 x **Silkcoat Dahili Acrylic Paste** (in case surfaces need smoothing)
4. 1 x **Silkcoat Putty Primer** (in case of old putties on surfaces)
5. 1 x **Silkcoat Izolac Pack** (where the surface is gypsum plaster)
6. 1 x Roller and Brush (for primer and **Metalico** application)
7. 1 x **Metalico** Decorative Application Tool
8. 2 x Drop sheets (for floor and furniture protection)
9. 2 x Masking Tape Rolls
10. 6 x sheets sandpaper (2 x 100 grain, 2 x 80 grain, 2 x 70 grain)
11. 1 x sanding block

## APPLICATION INSTRUCTIONS

### INSTRUCTIONAL VIDEOS

<https://www.youtube.com/watch?v=9sNKfd-u724>

<https://www.youtube.com/watch?v=0ycxAbY8TsI>



**RJ Works Sdn Bhd**  
(762722-K)  
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.  
Tel : 03-78317087 Website : [www.rjworks.com.my](http://www.rjworks.com.my)

#### **SURFACE PREPARATION:**

- The surface must be cleared of any oil, dirt or dust and swollen and old paintings must be scraped off - surface must be clean, dry and solid.
  - In case the surface is not smooth, first apply **Silkcoat Dahili Acrylic Paste for Metalico** to obtain a problem-free surface for topcoat application
- If the surface to be applied is flattened with gypsum plaster, use **Silkcoat İzolac** on the surface
- Smooth but old painted, synthetic and dirty surfaces should be obtained by applying **Silkcoat Universal Primer**; a surface which has been puttied should be prepared by applying **Silkcoat Putty Primer**

#### **PRODUCT PREPARATION:**

1. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying
2. Before using **Metalico**, add water to thin the **Metalico** to your desired effect
3. Mix until it becomes completely homogenous
4. If applied on very bright and glassy surfaces, a solid surface should be formed by sanding the surface first to ensure better adhesion.



**RJ Works Sdn Bhd**  
(762722-K)  
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.  
Tel : 03-78317087 Website : [www.rjworks.com.my](http://www.rjworks.com.my)

## APPLICATION:

1. Place drop sheets on floor and over any exposed furniture under surface to be painted
2. Apply masking tape to all corners and edges at boundaries of areas to be painted
3. Apply single layer of **Acrylic Paste** (where surface is not smooth)
4. Apply single layer of **Primer** and wait a minimum of 30 minutes for drying
5. Apply 1<sup>st</sup> layer of Silkomatt or Class Plastic and allow to dry then apply 2<sup>nd</sup> layer
6. After the Silkomatt or Class Plastic coats are dry, 1 coat of **Metalico** is applied thinly (up to 20 – 30 m<sup>2</sup> / 210 – 320 sq ft) by use of roller and brush
7. Immediately on application (DO NOT ALLOW TO DRY), use the application pattern tool to “stamp” the **Metalico** effect onto the paint
  - a. NB: **Metalico** dries very fast so best to have 2 people working on wall – 1 to use roller, 1 to follow with the **Metalico** tool for the effect
8. After application, tools should be cleaned with water.

## SAFETY AND PERSONAL PROTECTION DURING USE

- Avoid getting eye and skin contact. In case of contact, wash with plenty of water
- Preserve in a tightly closed container and keep out of the reach of children

## SAFE DISPOSAL OF WASTES

- Dispose of properly by washing all equipment and disposing of buckets etc in plastic recycling unit – DO NOT DUMP INTO SEWER SYSTEM

## STORAGE:

- Keep in a cool and clean place away from direct sunlight NB: It can be stored unopened 1 year at room temperature