



RJ Works Sdn Bhd
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my



Silkcoat Effect Paints

Metalico Soft Paint

3kg Client Information

Pack (100 sq ft)

DESCRIPTION: **Metalico Soft** is a **decorative paint**. It is a Pure Acrylic Emulsion binder based, psoriasis additives, pearl elegance decorative interior wall paint.

CHARACTERISTICS:

- Harmless to people and environmental friendly through its water based content
- Thanks to its nacre structure, **Metalico Soft** offers a bright and special look like pearl, allowing for different pattern applications.
- High covering ability and leaves no cracks
- Easy cleanable through glassy surface.

APPLICATION SURFACES:

After surface preparation, **Metalico Soft** can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

TECHNICAL INFORMATION

Structure: Pure Acrylic

Coverage (for 3 kg): 9 m² / 100 sq ft

Thinner: No thinning, ready to-use



RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

Drying: Touch dry: after 15-20 min, Dust repulsive: after 1-1.5 hour, Hard dry: after 24 hours

PACKAGE

Package Includes:

1. 1 x 3 litre of **Metalico Soft Effect Paint** (160 sq ft)
2. 1 x **Metalico Soft Primer Pack** for 160 sq ft
3. 1 x **Silkcoat Internal Acrylic Putty Pack** (in case surfaces need smoothing)
4. 1 x **Silkcoat Paste Primer** (in case of old putties on surfaces)
5. 1 x **Silkcoat Izolac Pack** (where the surface is gypsum plaster)
6. 1 x Roller and Brush (for primer and Metalico Soft application)
7. 1 x **Metalico Soft** Decorative Application Tool
8. 2 x Drop sheets (for floor and furniture protection)
9. 2 x Masking Tape Rolls
10. 6 x sheets sandpaper (2 x 100 grain, 2 x 80 grain, 2 x 70 grain)
11. 1 x sanding block



APPLICATION INSTRUCTIONS

INSTRUCTIONAL VIDEOS

https://www.youtube.com/watch?v=zZsqV7L_ILs

https://www.youtube.com/watch?v=Gk_qD_6SQBk



SURFACE PREPARATION:

- The surface must be cleared of any oil, dirt or dust and swollen and old paintings must be scraped off - surface must be clean, dry and solid.
 - In case the surface is not smooth, first apply **Silkcoat Dahili Acrylic Paste for Metalico application** to obtain a problem-free surface for topcoat application
- A smooth and glazed surface can be obtained by applying **Silkcoat Izolac before Metalico Soft application**
- Smooth but old painted, synthetic and dirty surfaces should be obtained by applying **Silkcoat Universal Primer**
- A surface which has been puttied should be prepared by applying **Silkcoat Putty Primer**

PRODUCT PREPARATION:

1. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying
2. Before using **Metalico Soft**, it should be mixed until it becomes completely homogenous
3. If applied on very bright and glassy surfaces, a solid surface should be formed by sanding the surface first to ensure better adhesion.

APPLICATION:

1. Place drop sheets on floor and over any exposed furniture under surface to be painted
2. Apply masking tape to all corners and edges at boundaries of areas to be painted
3. Silkcoat **Metalico Soft** can be applied (without diluting) by use of decorative trowel in two coats
4. Leave minimum 4 hours between coats depending on weather conditions
5. After 2nd coat application is dry, **Metalico Soft** is applied with trowel without diluting again giving both diagonal and vertical-horizontal non-continuous trowel strikes to make the material textured on the surface
6. As a last step, the entire surface is shined by putting pressure on the trowel with up-down and right-left circular movements



RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

7. After application, tools should be cleaned with water.

SAFETY AND PERSONAL PROTECTION DURING USE

- Avoid getting eye and skin contact. In case wash with plenty of water
- Preserve in a tightly closed container
- Keep out of the reach of children

SAFE DISPOSAL OF WASTES

- Dispose of properly by washing all equipment and disposing of buckets etc in plastic recycling unit – DO NOT DUMP INTO SEWER SYSTEM

STORAGE:

- Keep in a cool and clean place away from direct sunlight NB: It can be stored unopened 1 year at room temperature