



RJ Works Sdn Bhd
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my



Silkcoat Effect Paints Velveto Soft Paint 3kg Client Information Pack (100 sq ft)

DESCRIPTION: **Velveto Soft Silkcoat Effects Group** is a series of psoriasis-added, velvet-patterned, shiny appearance, pure acrylic-based, creating fun and moving spaces.

CHARACTERISTICS:

- **Velveto Soft** allows different pattern applications.
- It offers a nacre semi-gloss and matt-like pearl special appearance.
- Due to its water-based structure, it does not harm human health or the environment.

APPLICATION SURFACES:

All pre-painted surfaces can be applied to interior surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

TECHNICAL INFORMATION

Coverage (for 3kg): 9 m² / 100 sq ft

Thinner: No thinning, ready to-use

Drying: Touch dry: after 30-45 min, Dust repulsive: after 1-1.5 hour, Hard dry: after 24 hours

PACKAGE

Package Includes:

Rosaline 0199000188 Email : rosalin@rjworks.com.my
Dennis 0169839715 Email: mcmderr@rjworks.com.my
www.rjworks.com.my





RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

1. 1 x 3kg of **Velvetto Soft Effect Paint** (100 sq ft)
2. 1 x **Velvetto Soft Primer Pack** for 100 sq ft
3. 1 x **Silkcoat Putty Primer** (in case of old putties on surfaces)
4. **1 x Silkcoat Internal Acrylic Putty**
5. **1 x Silkcoat İzolac**
6. **1 x Silkcoat Universal Primer**
7. 2 x **Velvetto Soft** Application Decorative Trowel
8. 2 x Drop sheets (for floor and furniture protection)
9. 2 x Masking Tape Rolls
10. 6 x sheets sandpaper (2 x 100 grain, 2 x 80 grain, 2 x 70 grain)
11. 1 x sanding block

APPLICATION INSTRUCTIONS

INSTRUCTIONAL VIDEOS

<https://www.youtube.com/watch?v=FAiv-hl7eAs&t=8s>

<https://www.youtube.com/watch?v=WnHcu-x0KCo>



SURFACE PREPARATION:

- The surface must be cleared of any oil, dirt or dust and swollen and old paintings must be scraped off - surface must be clean, dry and solid.
- If necessary, defects and cracks on the surface should be repaired with **Silkcoat Internal Acrylic Putty**.
- If the surface to be applied is flattened with gypsum plaster, **Silkcoat İzolac** should be used on the surface before Silkomatt application,
- Use **Silkcoat Universal Primer** on old painted, dirty or synthetic painted surfaces,
- **Silkcoat Putty Primer** should be used on surfaces with putty application.
- **Silkomatt** is applied as a single layer on the last layer of the same color of **Velvetto Soft**. **Velvetto Soft** is applied to the surface with the help of roller. The pattern is given to the product by circular movements with the help of a special trowel, without complete drying on the surface.
- The surface is left to dry for 4-6 hours depending on weather conditions. After the first layer application is applied, the second layer is applied with the help of a **Velvetto Soft** decorative trowel or roller to form a thin layer on the surface.
- After application, the surface is patterned with circular motions with the help of special trowel. Tools should be cleaned immediately after application.

PRODUCT PREPARATION:

1. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying
2. Before using **Velvetto Soft**, it should be mixed until it becomes completely homogenous
3. If applied on very bright and glassy surfaces, a solid surface should be formed by sanding the surface first to ensure better adhesion.



RJ Works Sdn Bhd
(762722-K)
Construction work / Durable wall and floor coating from Turkey

27, Jalan PJU 1A/20A, Ara Damansara 47301, Petaling Jaya, Selangor D. E.
Tel : 03-78317087 Website : www.rjworks.com.my

APPLICATION:

1. Place drop sheets on floor and over any exposed furniture under surface to be painted
2. Apply masking tape to all corners and edges at boundaries of areas to be painted
3. Silkomatt is applied as a single layer on the last layer of the same color of **Velvetto Soft**. **Velvetto Soft** is applied to the surface with the help of roller. The pattern is given to the product by circular movements with the help of a special trowel, without complete drying on the surface.
4. The surface is left to dry for 4-6 hours depending on weather conditions. After the first layer application is applied, the second layer is applied with the help of a **Velvetto Soft** decorative trowel or roller to form a thin layer on the surface.
5. After application, the surface is patterned with circular motions with the help of special trowel.
6. Tools should be cleaned immediately after application.

SAFETY AND PERSONAL PROTECTION DURING USE

- Avoid getting eye and skin contact. In case wash with plenty of water
- Preserve in a tightly closed container
- Keep out of the reach of children

SAFE DISPOSAL OF WASTES

- Dispose of properly by washing all equipment and disposing of buckets etc in plastic recycling unit – DO NOT DUMP INTO SEWER SYSTEM

STORAGE:

- Keep in a cool and clean place away from direct sunlight NB: It can be stored unopened 1 year at room temperature